## This Page Is Inserted by IFW Operations and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

## IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

## PATENT ABSTRACTS OF JAPAN

(11) Publication number: 2000145467 A

(43) Date of publication of application: 26.05.00

(51) Int. CI

F02B 31/00

F02B 17/00

F02D 9/02

F02M 69/32

F02D 41/04

F02F 1/42

(21) Application number: 11098178

(71) Applicant:

YAMAHA MOTOR CO LTD

(22) Date of filing: 05.04.99

(72) Inventor:

ISAKA YOSHIHARU SUZUKI SADAHIDE

(30) Priority:

07.09.98 JP 10252352

(54) INTAKE SYSTEM FOR ENGINE

(57) Abstract:

PROBLEM TO BE SOLVED: To stabilize combustion under a low load operation by a tumble even when an air-fuel mixture is lean and increase output under a high load operation by enlarging a cross-sectional area of a duct of an inlet port.

SOLUTION: To a cylinder head 2 having two inlet valves 7 per cylinder, a spark plug 12 is disposed on a side of one of the inlet valves. An inlet port 9 is supplied with an air-fuel mixture from a carburetor 15. A wall 22 which partitions an intake duct downstream of a throttle valve into a throttle valve open side and a throttle valve close side is formed in the carburetor 15. The throttle valve open side is connected to a side of a cylinder body 3 at the end of an upstream of the inlet port 7 through a high load duct 16. The throttle valve close side is connected to a portion which is on a side of a valve cam chamber 5 at the end of the upstream of the inlet port 9 and extends toward the other inlet valve 7 on the side of the spark plug 12.

COPYRIGHT: (C)2000, JPO

